

Safety Data Sheet

according to 91/155/EEC and ISO 11014-1

Date of printing: 01.07.2005

Page: 1/5

Revised: 10.09.2004

SDS No.: 057-00217662.0000

1. Identification of the substance/preparation and company

Product

Product name

SikaForce-7325 L12 GR (formerly 2054)

Manufacturer/supplier information

Manufacturer/supplier:

Sika Danmark A/S

Street/postbox:

Præstemosevej 2-4

Town/City and Post Code:

DK-3480 Fredensborg

Country:

Danmark

Phone:

(0045) 48 18 85 85

Telefax:

(0045) 48 18 84 96

General information:

-

Emergency information phone:

Giftinformations centralen

(Bispebjerg Hospital) telefon 35 31 60 60

2. Composition/information on ingredients

Chemical characterization

Modified polyol

Hazardous ingredients

Designation according to 67/548/EEC

CAS No. Concentration Danger symbols R phrases

EC No.

- Solvent naphtha (petroleum), light arom.

64742-95-6

0.1 - 1 %

N,Xn

51/53,10,65,37,66,67

265-199-0

3. Hazards identification

See chapter 11 and 12

4. First-aid measures

National regulations

General instructions

In any case show the physician the Safety Data Sheet

After inhalation

In the event of symptoms take medical treatment.

After skin contact

In case of contact with skin wash off immediately with soap and water

Consult a doctor if skin irritation persists.

After eye contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.

Product name: SikaForce-7325 L12 GR (formerly 2054)

Date of printing: 01.07.2005

Page: 2/5

Revised: 10.09.2004

SDS No.: 057-00217662.0000

4. First-aid measures (continued)

Summon a doctor immediately.

After ingestion

Do not induce vomiting.

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

compatible with all usual extinguishing media

Exposure hazard arising from the product, its combustion products or resulting gases

In the event of fire the following can be released:

Carbon monoxide (CO)

Carbondioxide (CO₂)

Nitrogen oxides (NO_x)

Additional information

Fire residues and contaminated firefighting medium must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures for cleaning up

Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

When picked up, treat material as prescribed under heading "Disposal".

Product name: SikaForce-7325 L12 GR (formerly 2054)

Date of printing: 01.07.2005

Page: 3/5

Revised: 10.09.2004

SDS No.: 057-00217662.0000

7. Handling and storage

Handling

Instructions for safe handling

See chapter 8 / Personal protective equipment.

Instructions for fire and explosion protection

Not applicable.

Storage

Requirements for storage rooms and containers

Keep container tightly closed and dry in a cool, well-ventilated place

Combined storage instructions

Keep away from food, beverages and animal feedstocks.

Additional information regarding storage

Protect from frost.

Protect from heat and direct sunlight

Protect from atmospheric moisture and water

8. Exposure controls/personal protection

Personal protective equipment

General protective and hygiene measures

Take care for sufficient ventilation or exhaust on the workshop place.

Avoid contact with eyes and skin

Use barrier skin cream.

Remove soiled or soaked clothing immediately.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

Respiratory protection

Not applicable.

Hand protection

Butyl rubber/nitrile rubber gloves

Eye protection

Safety glasses

Body protection

Working clothes

9. Physical and chemical properties

Product name: SikaForce-7325 L12 GR (formerly 2054)

Date of printing: 01.07.2005

Page: 4/5

Revised: 10.09.2004

SDS No.: 057-00217662.0000

9. Physical and chemical properties (continued)

Appearance

Physical state: liquid

Colour: grey

Data relevant to safety

Flash point > 101 °C

Method

Density at 20°C approx. 1.3 g/cm³

Solubility in water insoluble

Viscosity at 20°C approx. 6000 mPas

VOC (solvents) 0.29 %

VOC (CH) 0.29 %

10. Stability and reactivity

Materials to avoid/dangerous reactions

No hazardous reactions when stored and handled according to prescribed instructions.

Thermal decomposition and hazardous decomposition products

No decomposition if used as prescribed.

11. Toxicological information

Experience on humans

When skin contact:

May cause irritation.

When eyes contact:

May cause irritation.

When inhalation:

May cause irritation.

When swallowed:

May cause health disorders.

12. Ecological information

Additional information

Do not allow to enter waste water drain, waterways or soil.

Product name: SikaForce-7325 L12 GR (formerly 2054)

Date of printing: 01.07.2005

Page: 5/5

Revised: 10.09.2004

SDS No.: 057-00217662.0000

13. Disposal considerations

Packaging

Recommendations

Completely emptied packagings can be given for recycling.

Packaging containing remains of dangerous substances, as well as packagings disposed of remains can be unharmed eliminated in accordance with the regulations.

14. Transport information

ADR/RID

Further information

No dangerous goods.

IMO/IMDG

Marine pollutant: no

Further information

No dangerous goods.

IATA/ICAO

Further information

No dangerous goods.

15. Regulatory information

Labelling according to EEC Directive

The product does not require a hazard warning label in accordance with EC directives/the relevant national laws.

16. Other information

asterisk (*) on left margin marks modification of previous version

Recommended use: Chemical product for construction and industry

R-phrases of the ingredients listed in chapter 2

10 Flammable.

37 Irritating to respiratory system.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed

66 Repeated exposure may cause skin dryness or cracking

67 Vapours may cause drowsiness and dizziness

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to any use and processing.