

Product Info

Aerials | Dishes | Mast amplifiers | Mast combiners | Single channel filters | Notch filters | Stacking combiners | Passives | Mounting accessories

Triax C-HD 415 CX DVB-C MPEG-4 set top box

DVB-C MPEG-4 receiver with embedded Conax and AC3 sound system

Features

- DVB-C receiver, MPEG-4 HD, H.264
- User friendly 7 days EPG function
- User friendly on screen display
- HDMI output, perfect for flat screen TV
- **USB support** for easy programming
- SCART and audio outputs
- Supports both 12V and 230 V
- Fast text TV function
- Timer function
- Scandinavian Design
- Power consumption: 10 W
- Stand by power consumption: 0,5 W



On/off
IR-eye
Program step up/down

Conax cardreader



Connector for DVB-C signal

RF connector for tv/video

USB connector for easy programming and/or external harddisk

Phono connector

Scart for tv/video

External power supply

HDMI connector – brings crystal clear pictures, on even the largest flat-screen





Technical specifications

Triax C-HD 415 CX DVB-C MPEG-4 set top box

| Type Art No. | Triax C-HD 415 CX 305041 |
|------------------------------------|---|
| Tuner & Channel | Input connector: IEC - 169 - 2; Female |
| | Input frequency range: 47 to 862 MHz |
| | Input impedance: 75 Ω unbalanced |
| | Demodulation: QAM 16 / 32 / 64 / 128 / 256 |
| | Symbol rate: 1 - 10 Msym/s |
| MPEG Transport Stream A/V Decoding | Transport stream: MPEG-2 ISO / IEC 13818 |
| | Profile level: MPEG-2 MP@HL, H.264 MP and HP level 4.1 |
| | Input rate: Max. 100 Mbit/s |
| | Aspect ratio: 4:3 / 16:9 |
| | Audio decoding: MPEG Layer I & II, Optional Dolby Digital, DTS or AAC |
| A/V Data In/Out | Sampling rate: 32, 44.1, and 48 kHz |
| | Audio connectors: L/R analog, coax SPDIF |
| | Video connectors: HDMI, SCART |
| | HDMI connector |
| | Resolution: 576i, 576p, 720p, 1080i |
| Processor and Memory | Flash memory: 4 Mbyte DDR memory: 96 Mbyte |
| | CPU: STI 7101 |
| Power supply | Input voltage: 230 VAC \pm 15% |
| | Power consumption: Max. 10 W |
| | Type: External SMPS |
| | Standby consumption: Max. 0,5 W |

TRIAX A/S

Bjørnkærvej 3 • DK-8783 Hornsyld
+45 76 82 22 00 • +45 75 68 79 66
mail: triax@triax.dk • www.triax.com



TRIAX - your ultimate connection